



DATA SHEET

Rust-Lok

ULTRADEC

#12 Tenbrook Industrial Park – Arnold, MO 63010

Office 636.296.2900 Fax 636.296.2904

www.ultradec.com info@ultradec.com

DESCRIPTION:

A one component, metallic pigmented Moisture Cured Urethane (60% Solids). It may be applied directly to rusted surfaces, binding in the old rust and providing years of protection. Coated panels showed no sign of rusting after 2,000 hours in 5% Salt Water Solution (Salt Fog Machine). By eliminating costly sandblasting and exotic coating systems, RUST-LOK provides a very economical system that is tough, flexible and extremely durable.

USE:

Equipment, machinery, bridge structures, tanks barges, and most any metal surface. May also be used as a prime coat to prevent rusting on new metal. Has excellent intercoat adhesion

APPLICATION:

Remove loose scaly rust and be sure surface is reasonably dry. Apply at 45 mils with spray. Where brushing or rolling, a second coat may be applied almost as soon as you finish the first coat. When using as a prime coat, re-coat within one week.

MIXING:

Stir thoroughly and apply by brush, roller or spray.

COVERAGE:

Spray – 200 sq ft/gal

Brush/Roller – 300 sq ft/gal

DRY TIME:

1-2 hours

CLEAN UP:

Methyl Ethyl Ketone (MEK)

SAFETY PRECAUTIONS:

Keep out of reach of children - Harmful if taken internally Provide proper and adequate ventilation - Avoid prolonged contact with skin After materials have been cleaned from skin, wash with soap and water - Exposure to vapors should be avoided for prolonged periods of time Keep away from open flames - No smoking in the application area.

NON-WARRANTY:

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without any warranties, expressed or implied, since conditions and methods of use of our product are beyond our control. We recommend that the prospective user determine the suitability of our materials for the intended use before adopting them.