

MATERIAL SAFETY DATA SHEET

Information Telephone #: (636) 296-2900

Ultradec, Inc.
#12 Tenbrook Industrial Park
Arnold, MO 63010

ALL CHEMICAL EMERGENCIES
1-800-255-3924

Issue Date: 10/01/2001

Product Code 8320 A

SECTION I - PRODUCT IDENTIFICATION

Product Code: 8320 A
Trade Name: Hydro Epoxy
Product Class: Activated Aliphatic Amine
Chemical Family: Water based epoxy emulsion curing agent
TLV:
HMIS Rating: Health = Fire = Reactivity =

SECTION II - INGREDIENTS

Ingredients	CAS#	%	TLV
Polyamine and Polyamine Resins			N E

SECTION III - PHYSICAL DATA

Boiling Point:	N/A	Vapor Density:	
Solubility In Water	Complete	Vapor Pressure At 20°C	
Volatile %:	71.5%	Specific Gravity:	1.2
Evaporation Rate:	N/A	Appearance:	Color varies, as product is available in decorative hues
Odor		pH:	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class:

Flash Point:

LEL:

UEL:

- ◆ **EXTINGUISHING MEDIA:**
- ◆ **SPECIAL FIREFIGHTING PROCEDURES:**
- ◆ **UNUSUAL FIRE & EXPLOSION HAZARDS:**

SECTION V - HEALTH HAZARD DATA

- ◆ **THRESHOLD LIMIT VALUE:**
Not Established
- ◆ **ROUTES OF ENTRY:**
 - Inhalation: Hazardous components have low volatility. In confined area with poor ventilation, vapors may cause mild irritation to respiratory tract; otherwise no harmful effects expected
 - Ingestion: Not a likely route of exposure under normal conditions of use, but small amounts may be ingested by eating, drinking or smoking with unwashed hands after handling product
- ◆ **EFFECTS OF OVEREXPOSURE:**
Prolonged or repeated contact may cause mild skin irritation, sensitization or allergic skin reaction. Contact may cause irritation to eyes. Not likely to produce adverse effects from inhalation or ingestion.
- ◆ **FIRST AID:**
 - Eye Contact: Flush with water for 15 minutes and get medical attention
 - Skin Contact: Remove contaminated clothing and shoes. Wash exposed areas with soap and water. If irritation persists, get medical attention
 - Inhalation: Remove to fresh air
 - Ingestion: Not necessary to induce vomiting, consult a physician

SECTION VI - REACTIVITY DATA

- STABILITY:** () Unstable (X) Stable
- ◆ **INCOMPATIBILITY:**
Strong Oxidizing Agents
 - ◆ **CONDITIONS TO AVOID:**
Storage at elevated or freezing temperatures, premature mixing with epoxy resins or mixing in other than recommended proportions
 - ◆ **HAZARDOUS DECOMPOSITION PRODUCTS:**
CO, CO₂, Aldehydes and other organics
 - ◆ **HAZARDOUS POLYMERIZATION:**
Will not occur

SECTION VII – FIRE AND SPILL / LEAK PROCEDURES

- ◆ **STEPS TO BE TAKEN IF MATERIAL IS SPILLED:**
Cover with absorbent such as sand and collect in containers for disposal. Residual resin may be removed using steam of hot soapy water. Use of Methylene Chloride or other solvents for cleanup poses a distinct hazard and should be avoided. Ventilate area thoroughly and eliminate all sources of ignition. Personnel removing spill should observe all precautions and use appropriate protective equipment
- ◆ **WASTE DISPOSAL PROCEDURES:**
Disposal in accordance with local, state and federal regulations Not a hazardous waste under RCRA
- ◆ **OTHER PRECAUTIONS:**

SECTION VIII - SPECIAL PROTECTION INFORMATION

- ◆ **RESPIRATORY PROTECTION:**
N/A
- ◆ **VENTILATION:**
Local exhaust recommended.
- ◆ **PROTECTIVE GLOVES:**
Cotton work gloves adequate if changed when saturated. Rubber or plastic gloves preferred to minimize skin contact
- ◆ **EYE PROTECTION:**
Chemical safety goggles
- ◆ **OTHER PROTECTIVE EQUIPMENT:**
Eyewash, safety shower, protective clothing and footwear as needed

SECTION IX - SPECIAL PRECAUTIONS

- ◆ **STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:**
- ◆ **PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**
Avoid all contact with eyes, minimize contact with skin and clothing. If applying material indoors or in a confined space, avoid breathing concentrated vapors and provide plenty of fresh air ventilation. If clothing becomes saturated with material, change rather than allowing prolonged skin contact. Launder contaminated clothing before reuse. Wash thoroughly after handling and before eating, drinking, smoking or using the toilet
Store in tightly closed containers in a cool, dry, well-ventilated area. Follow mix ratio on Product Data Sheet. Thoroughly stir both components before mixing, and continue to stir for at least 5 minutes after mixing to ensure even blending. Read Material Safety Data Sheet for both components before using. **DO NOT FREEZE!** Store above 32° F
- ◆ **WASTE DISPOSAL METHODS:**
Incineration or use other methods of disposal in accordance with local, state and federal regulations
- ◆ **OTHER PRECAUTIONS:**

SECTION X - SUPPLEMENTAL INFORMATION

- ◆ **REGULATORY INFORMATION:**
- ◆ **SARA SECTION 313 LISTED INGREDIENTS:**

PREPARED BY: Product Safety & Compliance Department
#12 Tenbrook Industrial Park
Arnold, Missouri 63010
(636) 296-2900

This information is provided in good faith and is correct to the best of Ultradec's knowledge as of the date hereof; however, Ultradec makes no representation as to its completeness or accuracy. Customers are encouraged to make their own determination as to the suitability of this product for their purpose prior to use. Ultradec disclaims responsibility for damages of any kind resulting from the use of this information. THERE ARE NO WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT IT DESCRIBES.
